

**KIT-BZ60-XKE (CS-BZ60XKE + CU-BZ60XKE)**



<b>BZ super-compact · R32</b>		
		<b>6.00 kW</b>
Kit		KIT-BZ60-XKE
Cooling capacity (Nominal)	kW	6,00
Cooling capacity (Min)	kW	0,98
Cooling capacity (Max)	kW	6,50
EER (Nominal) (1)	W/W	3,03
EER (Min) (1)	W/W	3,92
EER (Max) (1)	W/W	2,83
SEER (2)		6,30 A++
Pdesign (cooling)	kW	6,00
Input power cooling (Nominal)	kW	1,98
Input power cooling (Min)	kW	0,25
Input power cooling (Max)	kW	2,30
Annual energy consumption cooling (3)	kWh/a	333
Heating capacity (Nominal)	kW	6,80
Heating capacity (Min)	kW	0,98
Heating capacity (Max)	kW	8,00
Heating capacity at -7°C	kW	5,10
COP (Nominal) (1)	W/W	3,16
COP (Min) (1)	W/W	4,26
COP (Max) (1)	W/W	3,02
SCOP (2)		4,00 A+
Pdesign at -10°C	kW	4,40
Input power heating (Nominal)	kW	2,15
Input power heating (Min)	kW	0,23
Input power heating (Max)	kW	2,65
Annual energy consumption heating (3)	kWh/a	1.540
Indoor unit		CS-BZ60XKE
Indoor power source	V	230
Indoor recommended fuse	A	20
Indoor connection indoor / outdoor	mm <sup>2</sup>	4 x 2,5
Indoor air flow (Cool)	m <sup>3</sup> /min	12,7
Indoor air flow (Heat)	m <sup>3</sup> /min	13,6
Moisture removal volume	L/h	3,3
Indoor sound pressure (Cool -Hi) (4)	dB(A)	45
Indoor sound pressure (Cool -Hi) (4)	dB(A)	45
Indoor sound pressure (Cool -Lo) (4)	dB(A)	37
Indoor sound pressure (Cool -Q-Lo) (4)	dB(A)	34
Indoor sound pressure (Heat -Hi) (4)	dB(A)	45
Indoor sound pressure (Heat -Lo) (4)	dB(A)	37
Indoor sound pressure (Heat -Q-Lo) (4)	dB(A)	34
Indoor dimension (Height)	mm	290
Indoor dimension (Width)	mm	779
Indoor dimension (Depth)	mm	209
Indoor net weight	kg	9
Outdoor unit		CU-BZ60XKE
Outdoor air flow (Cool)	m <sup>3</sup> /min	42,6
Outdoor air flow (Heat)	m <sup>3</sup> /min	41,5
Outdoor sound pressure (Cool -Hi) (4)	dB(A)	50
Outdoor sound pressure (Cool -Hi) (4)	dB(A)	50

<b>BZ super-compact · R32</b>		<b>6.00 kW</b>
Outdoor sound pressure (Heat -Hi) (4)	dB(A)	50
Outdoor dimension (Height) (5)	mm	695
Outdoor dimension (Width) (5)	mm	875
Outdoor dimension (Depth) (5)	mm	320
Outdoor net weight	kg	43
Pipe diameter (Liquid)	Inch (mm)	1/4 (6,35)
Pipe diameter (Gas)	Inch (mm)	1/2 (12,70)
Pipe length range	m	3 ~ 30
Elevation difference (in/out) (6)	m	15
Pipe length for additional gas	m	7,5
Additional gas amount	g/m	15
Refrigerant (R32) / CO2 Eq.	kg / T	1,11 / 0,75
Operating range (Cool - Min)	°C	-10
Operating range (Cool - Min)	°C	-10
Operating range (Cool - Max)	°C	+43
Operating range (Heat - Min)	°C	-15
Operating range (Heat - Max)	°C	+24