



UltraEfficient LED bulb

MAS LEDBulbND4-60W E27 830 A60 FR G UE

This is the most efficient LED bulb from Signify. 210 lm/W helps to cement the company statement of sustainability. The 50,000 -our lifetime helps to extend the replacement cycle to reduce the waste. This is not only a high SPEC product, but it also maintains the light quality of the Philips brand

Product data

General information	
Cap base	E27 [E27]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	50000 h
Switching cycle	50,000X
	Sphere
Light technical	
Colour Code	830 [CCT of 3,000 K]
Luminous flux (nom.)	840 lm
Colour designation	White (WH)
Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	210 lm/W
Colour consistency	<6
Colour rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	4 W

Lamp current (nom.)	45 mA
Wattage equivalent	60 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	70 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Lamp Finish	Frosted
Bulb shape	A60 [A 60mm]
Approval and application	
Energy Efficiency Class	A
Energy consumption kWh/1,000 hours	4 kWh

UltraEfficient LED bulb


1099142

Product data

Full product code	871951443579700
Order product name	MAS LEDBulbND4-60W E27 830 A60 FR G UE
EAN/UPC – product	8719514435797
Order code	43579700

SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929003480002
Net Weight (Piece)	0.035 kg


Dimensional drawing




MAS LEDBulbND4-60W E27 830 A60 FR G UE

Product	D	C
MAS LEDBulbND4-60W E27 830 A60 FR G UE	60 mm	105 mm


Photometric data



General uniform lighting




Light Distribution Diagram



Spectral Power Distribution Colour

UltraEfficient LED bulb

Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram

