

JC50324

Emergency Exit Blade

Recessed suspended Exit Blade Maintained 3M IP20 without legend

Features & Benefits

- Visible from a distance of 24 metres
- Running man legend kits bought separately
- Suitable for use as maintained and non maintained
- Hinged frame for wall and ceiling mounting applications (JC50323 only)



General Information

Mounting	Recessed
Environment	Indoor
Suitable For Zones	Outside zone 2
Product Group	Emergency
Product Range	Exit Blade
Trade Name	Emergency Range
Color Finish	White
Product Shape	Rectangular
Product Weight(kg)	1.04
Overall Dimensions	300 x 535 x 65 mm
Light Source	LED
Light Source Features	Vibrant White
Additional Information	Viewing distance 35 metres
Luminaire Accessories	JC50308(left+right legend pack)JC50310(2 x down legend pack)JC50311(2 x Up legend pack)
Recommended Product Location	Recessed ceiling mount, indoor use only
Method Of Fix	Spring clips
Product Aperture Size	280 x 50mm

IP Rating	IP20
Origin of manufacturer	Made in China
Warranty	2 years standard warranty extends to 3 years when registered within the first year of purchase (2 years on batteries)(See Website for terms and conditions)
Operation Type	Maintained only
Mounting Height	Max 3 metres
Driver Manufacturer	JCC
LED Manufacturer/Type	Everlite 2835
Lighting Product Type 1	Emergency Lighting
Lighting Product Type 2	Recessed

Electrical

Voltage Rating	220-240
Primary Running Current(Amp)	0.022
Operating Frequency Hz	50/60Hz
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage	3W(AC)8.6W(DC)
Class	II
Input Electrical Connections	U/S live(brown or black),Neutral(blue)
Dimmable	No

Emergency Data

Load Voltage(DC)	12
LOR % in Emergency Mode	1
Inverter PFC	0.58

Battery Data

Battery Specification	3.6V,900mAh Ni Cd
Nominal Battery Current	900mAh
Charge Current	59-132mA
Recharge Time	24hrs
Battery run time	3hrs

Thermals

Operating Temperature Range °C	0 to +26
--------------------------------	-----------------

Performance Data

LED Life (Hours)	50000
------------------	--------------

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Actual Lumen Output	40 (AC) 40 (DC)
Lumens Per Circuit Watt	13 Lpcw(AC) 13 LpcW(DC)

Color Rendering Index	80-89
CRl: Ra	87
Correlated Color Temperature	6000K
LOR (Light Output Ratio) %	100
Photometry Available	yes

Construction




Primary Material	Polycarbonate
------------------	----------------------

Packaging

Product Packaged Weight(kg)	1.09
Quantity Per Outer Carton	10
Product Bar Code EAN-13 Number	5052544080593

Standards & Approvals

Manufactured In Accordance To	BS EN60598-2-22
CE Marked	yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE Symbol	yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015



JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 75 [04/01/2022]