

Product Code: CL050

Description: 13A Fused Connection Unit With Optional Flex Outlet



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad		
Finish	Metal Clad Grey		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Fuse Drawer & Housing:	Urea
	Terminals: Brass	Terminal Screws:	Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap:	Mild Steel
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Rating & Type	13A (BS 1362)		
Termination Type	Screw	Terminal Torque Value (Nm)	2
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	Flex Outlet Dimension (mm)	Ø10
Switched	No		
Twin Earth Terminals	Yes	Back Box Knockouts - Sides (mm)	1 x Ø20
Flex Outlet Available	Yes	Back Box Knockouts - Rear (mm)	None
Flex Outlet Location	Front of Plate		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	2 x Ø20		
Back Box Knockouts - Bottom (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.