

Product Code: OA412AGU

Description: 10AX 2 Gang 2 Way IP66 Weatherproof Switch Unit



**General Information**

<b>Dimensions (mm)</b>	91 (W) x 106 (H) x 72.5 (D)	
<b>Finish</b>	Anthracite Grey	
<b>Gasket Colour</b>	Black	
<b>Materials</b>	Cover, Housing & Clip: Polycarbonate Switch Membrane: Neoprene Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Seal & Gasket: Rubber Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
<b>Anti Microbial Certified</b>	No	
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Inductive Load Rating (AX)</b>	10	
<b>Load Rating Comments</b>	Suitable for Inductive Loads	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø3.5	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>2 Way Switch</b>	Yes	
<b>Back Box Knockouts - Total (mm)</b>	5 x Ø20	<b>Back Box Knockouts - Sides (mm)</b> 1 x Ø20
<b>Back Box Knockouts - Top (mm)</b>	1 x Ø20	<b>Back Box Knockouts - Rear (mm)</b> 1 x Ø20
<b>Back Box Knockouts - Bottom (mm)</b>	1 x Ø20	
<b>Ingress Protection</b>	IP66	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	5	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with 13A/10AX modules in the MiniGrid Range.

