

Product Code: EZTAG3

Description: Proximity and Keypad Door Entry



Component 1

EZTAG3 - Proximity & Keypad Door Entry

Quantity

1

Component 2

EZT3ST10 - Proximity Fobs

Quantity

10

General Information

Dimensions (mm)	150 x 44 x 24
Finish	Silver
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	< 50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

Environment

Ingress Protection	IP65
--------------------	------

General Information

Finish	Blue
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	< 50

Supplied Keypad and Mounting Bracket
Screws and Wall Plugs
Diode and Capacitor
User Manual
10 x fobs



Product Code: EZTAG3

Description: Proximity and Keypad Door Entry

Accessories

- EVBPSBB: 12V Lock power supply with battery backup
- EV-EXIT: Push to Exit Release Button
- EVEXITC: Contactless Exit button
- EVEXITM: Push to Exit Mushroom Release Button
- EXEVITMIP55: Push to Exit Mushroom Release Button IP55
- EV-EBG: Green Emergency Break Glass
- EXEBGEXT: External Emergency Break Glass
- ENTERD: Flush Electronic Lock
- ENTERD-YLR: Surface Electronic Lock
- EV-ML-250: Electromagnetic Lock
- EV-ML-500XT:

