TRT030DN

Digital Electronic Room Thermostat

Features & Benefits

- Easily adjustable dial
- Digital room temperature display, illuminated on setting
- Output LED (illuminated on call for heat)
- 5°C to 30°C set temperature range
- Temperature swing adjustment (using DIP switches) between a 0.5 °C and 1°C
- PID control
- Single pole, single throw (SPST) switch type
- Surface mount with wall plate included

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Connection	3 Wire
Setting Type	Dial
Set Temperature Range	5°C to 30°C, User Adjustable
ErP Product Class	Class 1
Boiler Type	3CYC (Gas) or 6CYC (Oil) Dip Switch Adjustable

TIMEGUARD®
A *theben* Group Company

additional information at:
https://www.timeguard.com

This data was generated on
17/05/2022

Subject to technical changes and misprints

Temperature Swing (Hysteresis)	1°C or 0.5°C
PID Control	Supported (ON/OFF Switchable)
Switch type	Single Pole, Single Throw (SPST)
Mounting Hole Centres (mm)	60
Switch rating	6A Resistive, 2A Inductive
Cable Entry(s)	Back Entry

General

Weight (g)	142.6
Height (mm)	86
Width (mm)	88
Depth (mm)	38
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Rawl Plugs, Screws
EAN Number	5012483014363
Guarantee Period	3 Years

TIMEGUARD®
A **theben** Group Company

additional information at:
https://www.timeguard.com

This data was generated on
17/05/2022

Subject to technical changes and misprints

Line Diagrams

TIMEGUARD®

A **theben** Group Company

Subject to technical changes and misprints

additional information at:
https://www.timeguard.com

This data was generated on

17/05/2022