



CorePro GLASS LED candles and lustres



CorePro LEDLuster ND 2.2-25W P45 E14 FRG

Featuring a classic heritage design, these filament LED candles combine the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb is a very easy choice for people who are looking for a retrofit LED replacement, it provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap base	E14
Nominal lifetime	15,000 h
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Colour Code	827 [CCT of 2700K]
Luminous Flux	250 lm
Luminous efficacy (rated) (nom.)	113.00 lm/W
Colour designation	Warm White (WW)
Correlated Colour Temperature	2700 K
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %
Flickering value (PstLM)	1
Stroboscopic effect	0.4

Photobiological safety according to EN 62471 RG1		
Operating and Electrical		
Line Frequency	50 to 60 Hz	
Input frequency	50 to 60 Hz	
Power Consumption	2.2 W	
Lamp current (nom.)	21 mA	
Wattage equivalent	25 W	
Starting time (nom.)	0.5 s	
Warm-up time to 60% light	0.5 s	
Power Factor (Fraction)	0.4	
Voltage (nom.)	220-240 V	
	-	
Temperature		
T-Case maximum (nom.)	36 ℃	


Datasheet, 2023, April 14 data subject to change

CorePro GLASS LED candles and lustres

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Lamp Finish	Frosted
Bulb shape	P45
Approval and Application	
Energy Efficiency Class	E
Energy consumption kWh/1,000 hours	3 kWh
EPREL registration number	387383
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
Can it be used in closed luminaires	No


CorePro LEDLuster ND 2.2-25W P45 E14	
FRG	
CorePro LEDLuster ND 2.2-25W P45 E14	
FRG	
871951434681900	
34681900	
929001345492	
1	
0.014 kg	
8719514346819	
10	
8719514346826	

Dimensional drawing




Product	D	С
CorePro LEDLuster ND 2.2-25W P45 E14 FRG	45 mm	80 mm

Photometric data








General uniform lighting - CorePro LEDLuster ND 2.2-25W P45 E14 FRG


CorePro GLASS LED candles and lustres


Photometric data



Light Distribution Diagram - CorePro LEDLuster ND 2.2-25W P45 E14 FRG

Lifetime





LEDbulb 25W E14 827 FR B35

Lumen Maintenance Diagram - CorePro LEDLuster ND 2.2-25W P45 E14 FRG



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.