

Luminaires | Downlights

Uni-FitCS™ Colour Switchable 15W Fixed Polycarbonate Dimmable Downlights

AU-DDL15CS



Photometrics

Wattage	15
Lumens	1400 - 1550
Lm/W	103
Beam Angle	100
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	<6
UGR19	NO

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK03
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Triac Dim
Dimmable	YES
Warranty	5 Years

Country of Origin	CN
-------------------	----

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.7
Surge Protection (kV)	1.5
Protection Class	CLASS TWO
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	NO

Physical Attributes

Height (mm)	60
Overall Diameter (mm)	150
Lamp Base	LED
Cutout Diameter Max. (mm)	120
Material	Polycarbonate
Optic Material	Polycarbonate
Diffuser	Opal
Finish Colour	White