

## **Technical Specification**



Product Code: VPSC523GY **Description:** 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon





## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian Finish Satin Chrome

> > 250

Insert Colour Grey Gasket Colour Grey

> Materials Front Plate: Stainless Steel Insert & Housing: Urea Switch Cover: Stainless Steel Neon Lens: Polycarbonate

Terminals: Brass Terminal Screws: Steel & Yellow Passivated

Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Gasket: Nylon

Earth Strap: Mild Steel

Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

> Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²)  $3 \times 2.5$ 

Anti Microbial Certified Rated Voltage (V~) (Ue)

> Double Pole Switch Yes Twin Earth Terminals Yes

Indicator Colour Red Neon Indicator Yes

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



E: sales@scolmore.com | W: scolmore.com