## essentials™

Product Code: OARCDP036

## **Technical Specification**

Description: 13A 2 Gang IP66 Weatherproof Type A Passive RCD Switched Socket



## **General Information**

Dimensions (mm) 158 (W) x 158 (H) x 90 (D)

Accessory Fixing Centres (mm) 120.6

Anthracite Grey

Cover, Housing & Clip: Polycarbonate Materials

Accessory Plate & Housing: Urea

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

PCB: Mixed Components

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 13

Breaking Capacity (A) 250 (Earth Leakage)

Through Fault Withstand (A)

Trip Speed Less than 40ms at 150mA Residual Current

Termination Type Screw

Terminal Size (mm) Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm<sup>2</sup>) 3 x 2.5 or 3 x 4

> Switched Yes

Single Pole Switched Yes

Twin Earth Terminals

Back Box Knockouts - Total (mm) 8 x Ø20

Back Box Knockouts - Top (mm) 1 x Ø20 Back Box Knockouts - Sides (mm) 2 x Ø20 Back Box Knockouts - Bottom (mm) 2 x Ø20 Back Box Knockouts - Rear (mm) 1 x Ø20

Ingress Protection IP66

Operational Temperature (°C) -5 to +40

Warranty (Years)

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



E: sales@scolmore.com | W: scolmore.com









Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Frequency (Hz) 50