

## **ECO PORTABLE UNITS**



## **ECO PORTABLE UNITS**

Cool down and relax anywhere with Midea energy efficient 'Eco Portable' air conditioners. With easy cleaning filters and water level protection, this air conditioner is easy to maintain and ensures a clean, healthy living environment.

#### **ENERGY SAVING**

Rated Energy Efficiency Class A, the PHA Portable Air Conditioner is designed to keep you cool and comfortable while saving energy. Its Eco-Design ensures energy efficiency, reducing energy consumption from 2W to just 0.5W while in standby mode, resulting in significant cost savings.

#### **SLEEP MODE FUNCTION**

With a precise temperature control system, "sleep mode" creates an ideal climate in your room so you can wake up comfortable and fully refreshed.

#### **AUTOMATIC RESTART**

In the event of a power failure, the unit restarts with the settings previously in use.

#### **EASY TO MOVE**

The unit sits on easy glide castor wheels, making it easy to transport and move the unit into different rooms.

#### **SELF EVAPORATING**

The water collected is automatically evaporated, so there is no need to worry about emptying trays.

#### **24 HOUR TIMER**

The timer function allows you to set a deferred switching on or off time with intervals up to 24 hours.











ECO timer

No Drain-Pipe Required

Easy to clean filter





Power cord tidy design

360° Castor Wheels

MIDEAUK.CO.UK





# ECO PORTABLE UNITS

### **ECO PORTABLE UNITS**

MODEL			MPPHA-07CRN7	MPPHA-09CRN7
Power supply (Powered via 3 Pin Plug)		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	7000	9000
	Capacity	KW	2.1	2.5
	Input	W	790	1000
	Current	А	3.45	4.5
	EER	W/W	2.6	2.6
	Energy Efficiency Class		А	А
Moisture Removal		L/h	1.797	1.94
Rated Input Consumption		W	960	1200
Rated Current		А	5	6.1
Starting Current		А	13	17
Indoor Air Flow (Hi/Mi/Lo)		m3/h	319/0/213	295/0/205
Indoor Side Noise Level (Hi/Mi/Lo)		dB(A)	52.5/0/47	52.5/0/47.5
Sound Power Level (Hi)		dB(A)	62	64
Power Consumption in Standby Mode		W	0.5	0.5
Refrigerant Type	Туре		R290	R290
	GWP		3	3
	Charged Quantity	kg	0.13	0.17
	CO2 Quantitiy	kg	0	0
Design Pressure		MPa	2.6/1.0	2.6/1.0
Plug Type			1.0x3/VDE	1.0x3/VDE
Control Type			Remote Control	Remote Control
Operation Temp (room temp)		°C	17-35	17-35
Dimension (W*D*H)		mm	329x318x634	329x318x634
Packaging (W*D*H)		mm	383x361x835	383x361x835
Net/Gross Weight		kg	21.5/24	23/25.53

