

AC Over Door Fan Heater



Technical Details

Controls	On-board controls
Controller functions	On / Off Two heat settings (Half Heat & Full Heat)
Installation	Included wall bracket
Construction / Finish	Pressed steel case with powder coated finish
Cable	None supplied
Approvals	CE, BEAB
IP Rating	IP21
Safety	2 x electrical hold reset cut-outs
Warranty	2 Years
Safety	2 x electrical hold reset cut-outs
IP Rating	IP21

Additional Information

Optimum mounting height 1.8m—2.3m

The AC range of over-door heaters are designed to provide a "warm welcome" over doorways. This product should not be specified for indoor space heating to reach and maintain a certain thermal comfort of human beings.


Product Description

Dimplex AC over door heaters provide multi-directional, powerful and effective heating above the entrance to shops, offices and almost any small doorway. When fitted above an open door, the warm airflow encourages trade by allowing doors and entrances to remain 'open for business' in many commercial applications.

Key Features

- Designed for localised heating around open doors
- Can be used as a high level fan heater
- Adjustable airflow direction
- Full heat, half heat and fan only settings
- Choice of 3kW, 4.5kW and 6kW
- 3KW and 4kW models designed for single doors
- 6KW model designed for double doorways

Dimensions



Model/Item No. (EAN-Code 501139+Item No.)	018250	018274	018281
	AC3N	AC45N	AC6N
Heat Output (kW)	1.3/3.0	2.25/4.5	3.0/6
Supply voltage	230V 1PN	230V 1PN	230V 1PN
Length A (mm)	605	605	905
Height (mm)	200	200	200
Depth (mm)	135	135	135
Air Velocity	6.2m/s	5.5m/s	8.3m/s
Noise dB(A)	50.5	52.0	57.0
Weight (kg)	5.1	5.2	7.2
Packaging Details			
Height (mm)	230	220	220
Width (mm)	730	720	1050
Depth (mm)	170	180	170
Weight (kg)	5.5	5.8	8
Ti	7	7	7
Hi	10	10	6
Pallet Quantity (2.4m high)	70	70	42