

JC72406

Skydisc IP20

Skydisc IP20 22W 4700K 1750Lm

Features & Benefits

- Polycarbonate construction
- Three sizes available
- Ultra low profile design
- Non-dimmable













General Information

Product Group

Product Range

Trade Name

Light Source

Light Source Features

Product Shape

Additional Information

Mounting

Product Weight

Color Finish

Overall Dimensions (mm) Rim

Recommended Product Location

Method Of Fix

Product Aperture Size

IP Rating

LED - Recessed

Skydisc IP20

Skydisc

LED

Cool White

Round

Not suitable for use with JCEM001ST

Recessed

0.405kg

White

Ø240mm

Interior Recessed

Spring Clips (supplied)

230mm

IP20

Environment Indoor

Luminaire Accessories Emergency remote pack JCEM001

Origin of manufacturer Made In China

2 years standard warranty extends to 3 years when

Warranty registered within the first year of purchase (See Website for

terms and conditions)

Driver Manufacturer JCC

LED Manufacturer/Type Runlite

Lighting Product Type 1 Downlight

Electrical

Voltage Rating 220-240
Secondary Running Current 275mA
Primary Running Current 161mA
Operating Frequency Hz 50/60Hz

CC or CV Constant Current

Luminaire Circuit Wattage 22

Class II: Double Insulated, no Earth required.

Output Voltage (V) 67.2-79.2VDC

EMC Compliant (EN55015)

Yes

Power Factor Correction

0.9

Input Electrical Connections Live & Neutral

Dimmable No

Thermals

Room Ambient Temperature Not To Exceed 30°C

Insulation Coverage Do not cover with insulation

Performance Data

LED Life (Hours) 30000

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Energy Rating This product contains a light source of energy efficiency class G

Actual Lumen Output 1750

Lumens Per Circuit Watt 80

Color Rendering Index 80-89

CRI: Ra 80

Correlated Color Temperature 4700K

Light Distribution Detail 120-degree

LOR (Light Output Ratio) % 100
Photometry Available Yes

Construction

Primary Material

Polycarbonate

Packaging

Product Packaged Weight

Quantity Per Outer Carton

Product Bar Code EAN-13 Number

0.52kg

40

5052544080432

Standards & Approvals

Manufactured In Accordance To

CE Marked

UKCA Marked

WEEE Symbol

Certificate Of Conformity

Accredited Members

BS EN 60598:2015, 2-1, 2-2


Yes


Yes

Yes

Yes: available on request.

LIA, ISO9001:2015, ISO14001:2015









JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 56 [23 Apr 2021]