

Product datasheet

Specifications



Lisse - Switched FCU - Flex Outlet - 13A DP with LED in Stainless Steel with BI

Local distributor code: 404917304 GGBL5013BSS

Main

Range	Lisse
Aesthetic name	Screwless deco
Product or component type	Fuse connection unit
Device presentation	Complete product
Colour tint	Interior: black Cover plate: stainless steel
Quantity per set	Set of 1

Complementary

Pilot light	without LED
Actuator	Rocker
Number of gangs	1 gang
Material	Stainless steel
Device mounting	Wall mounted
Fixing mode	Concealed screws
Rated current	13 A at 250 V AC
Connections - terminals	Screw terminals
Type of packing	Box
Width	87 mm
Height	87 mm
Depth	25 mm
Net weight	0.138 kg

Environment

Standards	BS 1363
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	169.7 g
Package 1 Height	3.3 cm
Package 1 width	9.2 cm
Package 1 Length	9.2 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Weight	17.452 kg
Package 2 Height	22 cm
Package 2 width	36 cm
Package 2 Length	48 cm
Unit Type of Package 3	PAM
Number of Units in Package 3	2400
Package 3 Weight	440.062 kg
Package 3 Height	115 cm
Package 3 width	100 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------