

## **Technical Specification**



## Product Code: VPAB522BK

Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet



**General Information** 



Plate Dimensions (mm) Dimensions With Gasket (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Insert Colour Gasket Colour Materials	88 (W) x 88 (H) x 8 (D) 91 (W) x 91 (H) x 9 (D) 60.3 Victorian Antique Brass Black Black Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon	Insert & Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Termin	nal Torque Value (Nm) 1.8
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate Flex O	utlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		

CECK

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (20/02/2 Errors & Omissions exclude piect to change without notic