essentials™

Product Code: CL052

Technical Specification

Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional

lex Outlet



General Information

Dimensions (mm) 80 (W) x 80 (H) x 42 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Metal Clad Finish Metal Clad Grey

Materials Insert, Switch, Fuse Drawer & Housing: Urea Neon Lens: Polycarbonate

Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Indicator Colour Red

Earth Strap: Mild Steel

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes

Double Pole Switch Yes

Twin Earth Terminals Yes

Neon Indicator Yes

Flex Outlet Available Yes

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Supplied Back Box Depth (mm) 40

Back Box Knockouts - Total (mm) 5 x Ø20

Back Box Knockouts - Top (mm) 2 x Ø20

Back Box Knockouts - Sides (mm) 1 x Ø20

Back Box Knockouts - Bear (mm) None

Back Box Earth Terminal Supplied Yes
Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

