

JC17072

Rechargeable Table Lamps

Round rechargeable lamp with charging base 2W IP54 3000K 168lm White

Features & Benefits

- Ideal for domestic applications, no electrician required
- This portable touch dimmable lamp allows for flexible illumination
- 6-8 hrs charge time, with up to 10 hrs run time at 100% light output
- The docking station is ideal for charging and convenient portability for use anywhere around the home
- Uses Lithium-ion batteries, increased charge and discharge cycles, for longer life span
- 3000K colour temperature to match the Architectural Exterior Range
- IP54 rating, suitable for exterior use





BEAM













General Information

Product Group

Product Range

IK Rating

Color Finish

Product Shape

Overall Dimensions

Light Source

Light Source Features

Additional Information

Origin of manufacturer

Warranty

LED Manufacturer/Type

Architectural Exterior

Rechargeable

IP54

White

Conical

280 x 110 Ø

LED

Warm White

UK USB Plug Adapter/ 1.2m USB charging lead pre-wired to

docking station.

China

2 years standard warranty extends to 3 years when

registered within the first year of purchase (2 years on

batteries) (See Website for terms and conditions)

Philips 3014

Electrical

Voltage Rating

220-240V~

Operating Frequency Hz

50/60Hz

Luminaire Circuit Wattage

Class II Plug Adapter, Class III luminaire

2

Battery Data

Battery Specification 2 * 18650 3.7V 2200mAh Lithium-ion

Battery Type

Nominal Battery Current

Charge Current

Lithium ion

4.4 Amp

1 Amp

Recharge Time (Mains USB) 6-8 hrs

Battery run time Running time(Light @Full Power) 10hrs.

Performance Data

LED Life (Hours) 36000

Hours life stated is an indication of expected L70 chip and light output calculations whenoperating in optimum conditions. Product warranty period supports the full productduring the term given. The L70 hours expectancy is not correlated with the full productwarranty term, nor is it a representation of lumen depreciation during the warrantyperiod.

Energy Rating

This product contains a light source of energy efficiency class

E

Actual Lumen Output

190

Lumens Per Circuit Watt

95
Standard Deviation Colour Matching - SDCM

>5
Color Rendering Index

CRI: Ra

84

Correlated Color Temperature 3000K

LOR (Light Output Ratio) % 100

Photometry Available Yes

Construction

Primary Material Aluminium

Lens Clear PC

Heat Sink Aluminium

Seal Material Silicon

Packaging

Quantity Per Outer Carton12Outer carton(L)- cm53.50Outer carton(W)- cm40.5Outer carton(H)- cm37.0Outer carton Net weight- kg5.76kgOuter carton Gross weight- kg10.80kg

Product Bar Code EAN-13 Number 5052544109430

Outer carton Bar Code ITF-14 Number 15052544109437

Standards & Approvals

Manufactured In Accordance To

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE Symbol

Certificate Of Conformity

Accredited Members





BS EN 60598-2015

Yes

Yes

Yes

Yes

Yes, available on request

LIA, IS09001:2015, IS014001:2015

JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jcc.co.uk | www.jc