

Technical Specification

Product Code: MD004PW

Description: 10AX 2 Way Retractive Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)	
Finish	Polar White	
Materials	Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Retractive Contact Options	Press to Make or Break	
Minimum Back Box Depth (mm)	16 (25 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges