



CorePro LEDlinear MV



CoreProLED linearD 17.5-150W R7S 118 840

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light that is just like a halogen lamp. Within the range, you can choose dimmable products which have deep a dimming function that enables a cosy ambience when using a dimmable fixture.

Product data

General Information	
Cap base	R7s
Nominal lifetime	15,000 h
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Colour Code	840 [CCT of 4000K]
Luminous Flux	2,460 lm
Luminous efficacy (rated) (nom.)	140.00 lm/W
Colour designation	Cool White (CW)
Correlated Colour Temperature	4000 K
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %
Flickering value (PstLM)	1
Stroboscopic effect	0.4
Photobiological safety according to EN 62471 RG1	
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz


Power Consumption	17.5 W
Lamp current (nom.)	90 mA
Wattage equivalent	150 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
Temperature	
T-Case maximum (nom.)	102 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb shape	Linear
Approval and Application	
Energy Efficiency Class	D
Suitable for accent lighting	No
Energy consumption kWh/1,000 hours	18 kWh
EPREL registration number	397598
CE mark	Yes

CorePro LEDlinear MV

EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
Can it be used in closed luminaires	No
Product Data	
Order product name	CoreProLED linearD 17.5-150W R7S 118 840
Full product name	CoreProLED linearD 17.5-150W R7S 118 840


Full EOC	871869964675200
Order code	64675200
Material no. (12 NC)	929002016702
Numerator – quantity per pack	1
Net Weight (Piece)	0.095 kg
EAN/UPC – Product/Case	8718699646752
Numerator – packs per outer box	10
EAN/UPC – Case	8718699646769

Dimensional drawing




Product	D	C
CoreProLED linearD 17.5-150W R7S 118 840	42 mm	118 mm

Photometric data




Spectral Power Distribution Colour - CoreProLED linearD 17.5-150W R7S 118 840



Light Distribution Diagram - CoreProLED linearD 17.5-150W R7S 118 840

CorePro LEDlinear MV


Photometric data




General Uniform Lighting - CoreProLED linearD 17.5-150W R7S 118 840

General uniform lighting - CoreProLED linearD 17.5-150W R7S 118 840

Lifetime



Lumen Maintenance Diagram - CoreProLED linearD 17.5-150W R7S 118 840



LEDspot R7S 230V

