

CorePro LEDlinear MV



CorePro LEDlinear ND 7.5-60W R7S 78mm840

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data


General Information		Input Frequency	
Cap-Base	R7S [R7s]	Input Frequency	50 to 60 Hz
Nominal lifetime	15,000 hour(s)	Power Consumption	7.5 W
Switching Cycle	50,000	Lamp Current (Nom)	70 mA
Lighting Technology	LED	Wattage Equivalent	60 W
Flux measurement reference	Sphere	Starting Time (Nom)	0.5 s
CE mark	Yes	Warm-up time to 60% light	0.5 s
EU RoHS compliant	Yes	Power Factor (Fraction)	0.5
		Voltage (Nom)	220-240 V
Light Technical		Temperature	
Color Code	840 [CCT of 4000K]	T-Case Maximum (Nom)	104 °C
Luminous Flux	1,000 lm		
Color Designation	Cool White (CW)	Controls and Dimming	
Correlated Color Temperature (Nom)	4000 K	Dimmable	No
Luminous Efficacy (rated) (Nom)	133.33 lm/W		
Color Consistency	<6	Mechanical and Housing	
Color rendering index (CRI)	80	Bulb Shape	Others
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Flickering value (PstLM)	1	Approval and Application	
Stroboscopic effect value (SVM)	0.4	Energy Efficiency Class	E
		Energy Consumption kWh/1000 h	8 kWh
		EPREL Registration Number	465220
Operating and Electrical			
Line Frequency	50 to 60 Hz		

CorePro LEDlinear MV

EyeComfort	Yes
Product Data	
Order product name	CorePro LEDlinear ND 7.5-60W R7S 78mm840
Full product name	CorePro LEDlinear ND 7.5-60W R7S 78mm840
Full product code	871869671396900
Order code	929001339102


Material Nr. (12NC)	929001339102
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696713969
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696713976

Dimensional drawing




Product	D	C
CorePro LEDlinear ND 7.5-60W R7S 78mm840	29 mm	78 mm


Photometric data



Accent Lighting Spots - CorePro LEDlinear ND 7.5-60W R7S 78mm840





Spectral Power Distribution Colour - CorePro LEDlinear ND 7.5-60W R7S 78mm840



Light Distribution Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

CorePro LEDlinear MV

Lifetime



Life Expectancy Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

Lumen Maintenance Diagram - CorePro LEDlinear ND 7.5-60W R7S 78mm840

