Xnightsbridge

DATASHEET



OP9RCD

IP66 13A 2G DP RCD Switched Socket - Type A (30mA)

www.mlaccessories.co.uk

MLA PART CODE	OP9RCD
DESCRIPTION	IP66 13A 2G DP RCD Switched Socket - Type A (30mA)
NET WEIGHT (KG)	0.798
FINISH	Black
DIMENSIONS (MM)	Height - 159 Width - 170 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK06
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
BUILT-IN TECHNOLOGY	Type A RCD
ADDITIONAL FEATURES	RCD trip current of 30mA. Latching type RCD.
FUNCTION	RCD trip speed of 30ms
CABLE ENTRY (MM)	9 x 20, 1 x 25
CABLE GLAND INCLUDED	No
WARRANTY	1year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270821345
D-1- O1- II 00/00/0000 44:40	

Date Created: 06/09/2022 14:49



