

HIGH CUT RESISTANT PU COATED GLOVE WITH RECYCLED POLYESTER

Dexterous high cut resistant PU palm coated glove with 25% rPET, glass and steel fibre free, touschscreen and reinforced on the thumb crotch...

FEATURES

- > High cut resistance: Level E (EN 388:2016) / ANSI A5
- > 15 gauge engineered HPPE with recycled polyester (25% of liner content) offers a unique sensation of comfort and protection
- > Steel and glass fibre free to avoid any risks of irritation
- > Durable PU palm coating ensures good protection against abrasion and secure grip in dry and greasy conditions
- > Reinforced thumb crotch enhances durability
- > Touchscreen capabilities to allow usage with screen devices
- > Seamless knit prevents irritation
- > RCS (Recycled Claim Standard) certified
- > 1 pair = 1 PET bottle of 500ml recycled
- > 18g of CO₂ reduced vs virgin polyester alternative











SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Metal Industry

Suitable Applications

- Assembling
- Handling Sharp and **Greasy Parts**
- Machining
- Bodywork
- Precision Mechanics
- Metal Stamping

CERTIFICATION







See overleaf for explanation







△SKYTEC Eco Rhodium[™]

PRODUCTION INFORMATION

MATERIALS	LINER:	15 gauge engineered HPPE, recycled polyester (25%)
	COATING:	Polyurethane (PU)
COLOUR	Grey/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00049BB SKG00049BD SKG00049BF SKG00049BH SKG00049BJ SKG00049BL	10 pairs per paper wrap 120 pairs per case


RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement $% \label{eq:continuous} % A = \{ (x,y) \in \mathbb{R}^{n} \mid (x,y) \in \mathbb{R}^{n} : y \in \mathbb{R$
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE				
Measured breakthrough time	Permeation performance index (grams)			
A1	≥ 200			
A2	≥ 500			
A3	≥ 1000			
A4	≥ 1500			
A5	≥ 2200			
A6	≥ 3000			
A7	≥ 4000			
A8	≥ 5000			
49	> 6000			

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

GLOBUS AMERICAS www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-RODIUM-1123_1

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834) UKCA Type-Examination Certificate issued by CCQS UKLtd. 25 Wilton Rd, Pimlico, London SWIV 1LW, United Kingdom. [UK Approved Body No. 1105].