

ULTRA LIGHTWEIGHT KNUCKLE COATED GLOVE WITH GREAT OIL GRIP

A very thin, flexible and dexterous knuckle coated glove offering oustanding tactility and grip in wet and oily conditions.

FEATURES

- Helps to protect the hand from oils, hydrocarbons, grease and abrasion to end of coated area
- > Supple and soft 18 gauge nylon liner provides excellent fingertips sensibility
- Nitrile sandy finish on palm offering excellent grip properties in wet and oily conditions
- > Designed for easy movement and continuous wear
- > Breathable back of hand to reduce perspiration
- > Seamless knit prevents irritation
- > Elasticated wrist provides a secure fit













SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Manufacturing

Suitable Applications

- Handling oily components
- Maintenance
- Wet works
- Assembly

CAT II CAT II EN 388:2016 ANSI/ISEA 105 AX 3 X See overleaf for explanation





△SKYTEC Oregon[™]

PRODUCTION INFORMATION

MATERIALS	LINER:	18 gauge nylon			
	COATING:	Nitrile sandy finish on smooth nitrile			
COLOUR	Blue / black				
LENGTH (mm)	250 (Size Dependent)				
CUFF STYLE	Elasticated knit wrist				

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00002DD SKG00002DF SKG00002DH SKG00002DJ SKG00002DL	10 pairs per paper wrap 120 pairs per case


RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for cut, thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS







 $\hbox{*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter}\\$

ANSI/ISEA 105-2016 ABRASION RATING CHART								
Abrasion Level Rating	0	1	2	3	4	5	6	
Gram Load	500	500	500	500	1000	1000	1000	
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000	

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)1618774747 F: +44 (0)1618774746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

offord Bark, Manahactar, M171SH LINITED KINGDOM

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-OREGON-1123_1

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA. Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)