

RILEY

LIGERA™ ECO

The first to market safety eyewear without single use plastic. Super lightweight Ligera™ ECO combines maximum wearer fit and comfort with a sleek sports design. A lightweight ECO solution, supplied in a microfibre pouch.



ULTRA
LIGHTWEIGHT



SOFT TPE



SPORTS
STYLE



AERO
TEMPLES

KEY FEATURES

- + Super lightweight 16.5g
- + Sleek sports design – 10 base curve & integral nose piece
- + Dual moulded temples with TPE temple ends for maximum fit and comfort
- + Anti-Scratch and Anti-fog dual coated UV400 Lenses
- + Panoramic lenses offer full wraparound protection and optimum vision
- + High-impact resistance under extremes of temperature (-5-55°C)
- + No single use packaging, supplied in a microfibre pouch made from 100% recycled material

| LENS | REF. | LENS MARKING | FRAME MARKING | PROTECTION AGAINST | COATINGS |
|-------|------------|---------------------------------------|---|------------------------|---|
| CLEAR | ○ RLY00494 | 2C-1.2 R 1FT CE / Z87+ U6 S/IO 0 | R EN 166 FT 2 CE / Z87+ / AS/NZS 1337.1 Lic. SMK40933 | Impacts, UV radiations | ARIDA 400 Anti-scratch + Anti-fog / UV400 / Moisture repellent |
| BLUE | ● RLY00495 | 2C-1.4 R 1FT CE / Z87+U6 S / I 1 | | | |
| LED | ● RLY00496 | 2C-1.4 R 1FTKN CE / Z87+U6 L1.3 / I 1 | | | |

GENERAL SPECIFICATION

| | |
|-----------|-------|
| LENS BASE | 10mm |
| WEIGHT | 16.5g |

PACKAGING

Individually contained microfibre pouch made from 100% recycled material

| | |
|------------|-----|
| PER BOX | 10 |
| PER CARTON | 200 |

COMPONENT SPECIFICATION

| COMPONENT | MATERIAL | FEATURES |
|-------------|--|--|
| LENS | Polycarbonate | Lightest weight Riley spectacle in range |
| NOSE BRIDGE | Thermoplastic Elastomers (TPE) | Co-injected - Durable and flexible, with secure and comfortable grip |
| TEMPLE | Polycarbonate / Thermoplastic Elastomers (TPE) | One piece moulded lens with side protection |
| HINGE | Polycarbonate / Metal | Sports styling |

LENS & FRAME MARKINGS

LENS MARKINGS

LENS FILTER TYPE:

2, 2C UV | 4 IR filter | 5, 6 Solar filter | 1.7 to 7 Welding filter if no shade number

SCALE NUMBER (SHADE):

1.2 Clear or Amber 1.4 Blue or I/O Waterproof
1.7 Minimises or I/O 2.5 Grey or Revo 3.1 Dark Grey or Mirror

 Identity of manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:


S Increased strength
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
A High energy impact, resists a 6mm, 0.86g ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

8 Short circuit electric arc
9 Molten metal splash
K Resistance to scratches by fine particles
N Resistance to fogging

 Certification mark

FRAME MARKINGS

 Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

S Increased strength
F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s
A High energy impact, resists a 6mm, 0.86 ball at 190m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE

3 Liquid droplets or splashes
4 Large dust particles > 5 µm
5 Gases and small dust particles < 5 µm
8 Short circuit electric arc
9 Molten metal and hot solids

  Certification marks

USA (ANSI)

LENS:

U6 UV (All lenses) L1.3 LED L1.7 Solar (I/O, Twilight)
L2.5 Solar (Grey) L3 Solar (Dark Grey) W4 Infrared lens

LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

AUS (AS/NZS)

LENS MARKINGS:

OCULAR CATEGORY:

0 UV 1 Solar 2 Solar
3 Solar O Outdoor untinted

MECHANICAL STRENGTH:

I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

FRAME MARKINGS:

AS/NZS 1337.1: 2010 guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by: UK - CCQS UK LTD. 25 Wilton Road, Pimlico, London, UK, SW1V 1LW [A.B. No. 1105].

EU - CCQS Certification Services Limited., Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin 15 D15 AKK1, Ireland [N.B. No. 2834]

Authorised Representative [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.



Standard Mark
(SAI Global)

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK

