

ALPHA SOTA L1



LOW ATTENUATION EAR DEFENDER

A low profile, lightweight ear defender with low attenuation, ideal for protection between 80 – 85DB. The L1 model features soft ear cushions and a flexible padded headband. Fully adjustable to provide a comfortable fit for most head sizes.

FEATURES

- ✓ SNR23
- ✓ Low profile cup design
- ✓ Large ear cushions allow freedom to fit majority of ears for a comfortable fit
- ✓ Padded, durable headband provides lasting comfort
- ✓ Very low attenuation ideal for protection at the first action level
- ✓ Blue in colour making them ideal for food environment
- ✓ Approved to EN352-1: 2002



ORDERING INFORMATION

Part Number: L1

Packaging: 1 Ear Defender per box
20 boxes per case

Certification: EN352-1: 2002

SUITABLE APPLICATIONS

An effective solution for those exposed to lower noise levels where hearing protection should be worn. Typical industries include;

- **Around Moving Machinery**
- **Building Sites**
- **Craft Work**
- **Engineering**
- **Food Processing**
- **Hand Drills**
- **Iron Processing**
- **Utilities and Highway Maintenance**
- **Oil and Gas**
- **Transportation**

ALPHA SOTA L1



LOW ATTENUATION EAR DEFENDER

TECHNICAL SPECIFICATIONS

ATTENUATION DATA

| Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|-------------------------|------|------|------|------|------|------|------|
| Mean Attenuation (dB) | 13.0 | 12.1 | 20.5 | 29.5 | 34.5 | 37.7 | 33.8 |
| Standard Deviation (dB) | 3.4 | 2.8 | 2.8 | 3.9 | 3.3 | 3.0 | 3.7 |
| Assumed Protection (dB) | 9.6 | 9.3 | 17.7 | 25.6 | 31.2 | 34.7 | 30.1 |

MATERIALS

| Component | Material |
|--------------------|---|
| Headband Cushion | Foam covered with PVC cloth & woven cloth |
| Headband Connector | ABS |
| Wire | Steel with chrome plated |
| Clip | ABS |
| Cup | ABS (with foam inside) |
| Cup Cushion | Foam covered with PVC cloth |
| Ring | ABS |

L1 EAR DEFENDERS
SNR = 23dB H = 30dB M = 20dB L = 13dB

Assumed Protection rounded to one decimal place

Results of tests performed in accordance with the standard BS EN352-1: 2002.

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: SATRA Technology Europe Limited, Bracetown Business Park, Clonee D15 YN2P, Republic of Ireland. [N.B. No.2777].

STORAGE & MAINTENANCE

Before use, always keep the ear defender in its original packaging and in a dry, clean, uncontaminated environment. To avoid potential damage, ensure the earpiece pads are not pressed together during storage.

Regularly inspect the ear defender for signs of damage and potential loss of sound attenuation. This product may be cleaned using a damp cloth and mild soapy water but not with chemicals. Allow to dry before use. Do not use abrasive cloths or brushes which may cause damage upon contact with any surface of the product. Further information can be obtained from the manufacturer.

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Alpha Solway Ltd

Part of
Globus
GROUP