

Sota L1

Low attenuation ear defender

A low profile, lightweight ear defender with low attenuation, ideal for protection between 80-85dB. The L1 model features soft ear cushions and a flexible padded headband. Fully adjustable to provide a comfortable fit for most head sizes.

Features

- ▲ SNR23
- ▲ Low profile cup design
- ▲ Large ear cushions allow freedom to fit majority of ears for a comfortable fit
- ▲ Padded, durable headband provides lasting comfort
- ▲ Very low attenuation ideal for protection at the first action level
- ▲ Blue in colour making them ideal for food environment
- ▲ Approved to EN352-1: 2002



Certifications

CAT III



EN 352-1:2002

EN 352-3:2020

Suitable industries & applications

Industries

- ▲ Construction
- ▲ Food Production
- ▲ Facilities Management
- ▲ Oil and Gas
- ▲ Automotive
- ▲ Highways and Infrastructure

Applications

- ▲ Machinery and Plant Operation
- ▲ Highway Repairs and Maintenance
- ▲ Masonry and Brickwork
- ▲ Craft and Hobbies
- ▲ Food Preparation and Handling
- ▲ Drilling and Boring

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747

Sota L1

Low attenuation ear defender

Frequencies Protection

Frequency (HZ)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	13	12.1	20.5	29.5	34.5	37.7	33.8
Standard Deviation (dB)	3.4	2.8	2.8	3.9	3.3	3	3.7
Assumed Protection (dB)	9.6	9.3	17.7	25.6	31.2	34.7	30.1

Ordering information

HME/ALP/SOTAL1	Items per Case 20 x Pieces
----------------	-------------------------------

Attenuation Data - SNR

Overall	High	Medium	Low
23dB	30dB	20dB	13dB

Additional information

Certification legend or click here	Declaration of conformity or click here	View product online or click here
--	---	---

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747