



RILEY

STREAM EVO

Frameless metal-free wraparound safety eyewear

The Riley Stream Evo is a lightweight safety spectacle with a secure fit, adjustable nose bridge, and flexible temple tips. Metal-free for electrical safety, it's slim for comfort with ear defenders and includes a microfiber pouch, making it perfect for manufacturing and construction.



TEMPFLEX



SOFT TPE



ADJUSTABLE
NOSE BRIDGE



ULTRA
LIGHTWEIGHT



DIELECTRIC



SPORTS STYLE

FEATURES

- + Single wraparound polycarbonate lens
- + Soft, adjustable, anti-slip nose bridge
- + Flexible temple tips
- + Co-injected bi-colour thermoplastic rubber temples provide a secure fit
- + Slim temples enhance comfort when worn with ear defenders
- + 1% metal free
- + Supplied with a microfibre storage pouch
- + Weight: 23g
- + 9.5-Base lens

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747



RILEY®

STREAM EVO

LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
SHADE 5	RLY00376	5 1 F K N CE / Z87+ W3	R EN166 FT CE UKCA Z87+	Impacts, UV Radiation, Infrared	TECTON 400
IRG	RLY00374	4 1 F K N CE W4		Impacts, UV Radiation, Infrared	
ANTI-REFLECTIVE	RLY00363	2C-1.2 1 FT CE U6 / IO 0	R EN166 FT CE UKCA Z87+ AS/NZS 1337.1 Lic. SMK40933	Impacts, UV Radiation	ARIDIA 400, UV400, Moisture Repellent
TWILIGHT	RLY00364	5-1.7 1 FT CE U6 L1.7 / I 1		Impacts, UV Radiation	
INDOOR/OUTDOOR	RLY00377	5-1.7 1 FT CE / Z87+ U6 L1.7		Impacts, UV Radiation	
GREY	RLY00362	5-2.5 1 FT K N CE U6 L2.5 / I 2		Impacts, UV Radiation, Solar Radiation	TECTON 400
CLEAR	RLY00361	2C-1.2 1 FT K N CE U6 / IO 0		Impacts, UV Radiation	
AMBER	RLY00371	2-1.2 1 FT K N CE U6 / IO 0		Impacts, UV Radiation	
LED	RLY00369	2C-1.4 1 FT K N CE U6 L1.3 / I 1		Impacts, UV Radiation	
BLUE	RLY00365	2C-1.4 1 FT K N CE U6 S / I 1		Impacts, UV Radiation	
SHADE 3	RLY00375	3 1 F K N CE / Z87+ W3 / I 3		Impacts, UV Radiation, Infrared	
TWILIGHT	RLY00360	5-1.7 1 FT / Z87+ U6 L1.7		Impacts, UV Radiation, Infrared	
			R FT CE	Impacts, UV Radiation	R Anti-Fog

GENERAL SPECIFICATION

WEIGHT	45g
--------	-----

PACKAGING

PER BOX	10
PER CASE	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL
LENS	Polycarbonate
NOSE BRIDGE	Thermoplastic Elastomers (TPE)
TEMPLE	Thermoplastic TR90, Thermoplastic Elastomers (TPE)
HINGE	Thermoplastic TR90, Metal

ADDITIONAL INFORMATION

CERTIFICATION LEGEND



or click [here](#)

DECLARATION OF CONFORMITY



or click [here](#)

VIEW PRODUCT ONLINE



or click [here](#)

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

salesusa@globusgroup.com
+1 83 337 54747

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary. Published date: 15/05/2025

GLOBUS