

**EXTENDED CUFF NITRILE CHEMICAL RESISTANT GAUNTLET**

SKYTEC CH202 features an heavyweight unlined nitrile gauntlet with extended cuff that's resistant to a range of solvents, animal fats and other chemicals.

**FEATURES**


- › Soft and flexible nitrile
- › Nitrile protects from oils, hydrocarbons and grease penetration
- › Sand patch finish allows secure handling in wet and dry conditions
- › Unlined to reduce risk of lint contamination
- › Embossed with the size for ease of pairing after laundering
- › Long cuff to protect the forearm and upper arm from chemical projections
- › Chlorinated to ease donning and doffing
- › Length: 48cm
- › Thickness: 0.55mm

**SUITABLE FOR****Typical Industries**

- Automotive
- Chemical
- Municipal Services
- Petrochemical
- Printing
- Waste Management

**Suitable Applications**

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying
- Refining

**CERTIFICATION**

See overleaf for explanation

## PRODUCTION INFORMATION

<b>MATERIALS</b>	LINER:	Unsupported, unlined
	COATING:	Nitrile
<b>COLOUR</b>	Green	
<b>LENGTH (mm)</b>	480	
<b>CUFF STYLE</b>	Gauntlet	

## ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKG00071ED	10 pairs per bag
8/M	SKG00071EF	
9/L	SKG00071EH	
10/XL	SKG00071EJ	60 pairs per case
11/XXL	SKG00071EL	

## RECOMMENDATIONS FOR USE

- **USE:** Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016  
PERFORMANCE LEVELS\*



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



PROTECTION AGAINST  
MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%		
D	Dichloromethane	M	65% Nitric acid	B	≥30 min for at least 3 chemicals
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide	C	≥10 min for at least 1 chemical
H	Tetrahydrofuran	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

## GLOBUS

### EUROPE

[www.globusgroup.com](http://www.globusgroup.com)

E: [sales@globus.co.uk](mailto:sales@globus.co.uk)

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

### MIDDLE EAST & AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

E: [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

T: +971 4 882 9962

F: +971 4 882 9963

### GLOBUS AMERICAS

[www.globusgroup.com](http://www.globusgroup.com)

E: [americas@globusgroup.com](mailto:americas@globusgroup.com)

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777).