



RILEY®

STREAM EVO

Frameless metal-free wraparound safety eyewear with a variety of lens options

The Riley Stream Evo is a lightweight safety spectacle with a secure fit, adjustable nose bridge, and flexible temple tips. Metal-free for electrical safety, it's slim for comfort with ear defenders and includes a microfiber pouch, making it perfect for manufacturing and construction.

	TWILIGHT		GREY
	CLEAR		AMBER
	LED		BLUE
	SHADE 3		SHADE 5
	ANTI-REFLECTIVE		INDOOR/OUTDOOR
	IRG		



ADJUSTABLE
NOSE BRIDGE



DIELECTRIC



SOFT TPE



SPORTS STYLE



TEMPFLEX



ULTRA
LIGHTWEIGHT

FEATURES

- + Single wraparound polycarbonate lens
- + Soft, adjustable, anti-slip nose bridge
- + Flexible temple tips
- + Co-injected bi-colour thermoplastic rubber temples provide a secure fit
- + Slim temples enhance comfort when worn with ear defenders
- + 1% metal free
- + Supplied with a microfibre storage pouch
- + Weight: 23g
- + 9.5-Base lens

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110



LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
SHADE 5	● RLY00376	5 1 F K N CE / Z87+ W3	REN166 FT CE UKCA	Impacts,UV Radiation,Infrared	TECTON 400
IRG	● RLY00374	4 1 F K N CE W4	Z87+	Impacts,UV Radiation,Infrared	
TWILIGHT	● RLY00364	5-1.7 1 FT CE U6 L1.7 / I 1	REN166 FT CE UKCA Z87+ AS/NZS 1337.1 Lic. SMK40933	Impacts,UV Radiation	ARIDA 400
INDOOR/OUTDOOR	● RLY00377	5-1.7 1 FT CE / Z87+ U6 L1.7		Impacts,UV Radiation	ARIDA 400
ANTI-REFLECTIVE	○ RLY00363	2C-1.2 1 FT CE U6 / IO 0		Impacts,UV Radiation	ARIDA 400, UV400, Moisture Repellent
GREY	● RLY00362	5-2.5 1 FT K N CE U6 L2.5 / I 2		Impacts,UV Radiation,Solar Radiation	TECTON 400
CLEAR	○ RLY00361	2C-1.2 1 FT K N CE U6 / IO 0		Impacts,UV Radiation	
AMBER	● RLY00371	2-1.2 1 FT K N CE U6 / IO 0		Impacts,UV Radiation	
LED	● RLY00369	2C-1.4 1 FT K N CE U6 L1.3 / I 1		Impacts,UV Radiation	
BLUE	● RLY00365	2C-1.4 1 FT K N CE U6 S / I 1		Impacts,UV Radiation	
SHADE 3	● RLY00375	3 1 F K N CE / Z87+ W3 / I 3		Impacts,UV Radiation,Infrared	
TWILIGHT	● RLY00360	5-1.7 1 FT / Z87+ U6 L1.7	FT CE	Impacts,UV Radiation	TECTON 400

GENERAL SPECIFICATION

WEIGHT	23g
--------	-----

PACKAGING

PER BOX	10
PER CASE	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL
LENS	Polycarbonate
NOSE BRIDGE	Thermoplastic Elastomers (TPE)
TEMPLE	Thermoplastic TR90, Thermoplastic Elastomers (TPE)
HINGE	Thermoplastic TR90, Metal

ADDITIONAL INFORMATION

CERTIFICATION LEGEND



or click [here](#)

DECLARATION OF CONFORMITY



or click [here](#)

VIEW PRODUCT ONLINE



or click [here](#)

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary. Published date: 25/07/2026