



RILEY®

READY READER

Adjustable magnifying eyewear in a sports style inspired frame

The Riley Ready Reader is an adjustable sports-style safety eyewear frame featuring 1.0 to 3.0 magnification inserts, lens positioning adjustments, comfortable dual-injected temples, a flexible nose bridge, and an impact-resistant UV filter lens, designed for precision work in various fields.

RILEY READY READER 1.00

RILEY READY READER 2.50

RILEY READY READER 3.00

RILEY READY READER 2.00

RILEY READY READER 1.50



INCLINABLE
TEMPLES



SPORTS STYLE

FEATURES

- + Available in 1
- + 1.5
- + 2
- + 2.5 & 3. magnifications
- + Adjustable ratchet to position reading lens
- + Soft flexible nosebridge for comfortable & secure fit
- + Sports wraparound styling to compliment plano safety eyewear

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110

LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
RILEY READY READER 1.00	RLY00510	2C-1.2 1 FT CE	R166 FT CE UKCA Z87+	Impacts,UV Radiation	ARIDIA 400 UV400, Moisture Repellent
RILEY READY READER 2.00	RLY00512	2C-1.2 1 FT CE		Impacts,UV Radiation	
RILEY READY READER 2.50	RLY00513	2C-1.2 1 FT CE		Impacts,UV Radiation	
RILEY READY READER 1.50	RLY00511	2C-1.2 1 FT CE		Impacts,UV Radiation	
RILEY READY READER 3.00	RLY00514	2C-1.2 1 FT CE		Impacts,UV Radiation	

GENERAL SPECIFICATION

WEIGHT	53g
--------	-----

PACKAGING

PER BOX	10
PER CASE	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL
LENS	Polycarbonate
FRAME	Polycarbonate
NOSE BRIDGE	TPR
TEMPLE	Polycarbonate, Thermoplastic Elastomers (TPE)

ADDITIONAL INFORMATION

CERTIFICATION LEGEND



or click [here](#)

DECLARATION OF CONFORMITY



or click [here](#)

VIEW PRODUCT ONLINE



or click [here](#)

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110