












# RILEY




## STREAM EVO

### Frameless metal-free wraparound safety eyewear

The Riley Stream Evo is a lightweight safety spectacle with a secure fit, adjustable nose bridge, and flexible temple tips. Metal-free for electrical safety, it's slim for comfort with ear defenders and includes a microfiber pouch, making it perfect for manufacturing and construction.

-  TWILIGHT
-  CLEAR
-  LED
-  SHADE 3
-  IRG
-  INDOOR/OUTDOOR
-  GREY
-  AMBER
-  BLUE
-  SHADE 5
-  ANTI-REFLECTIVE



-  ADJUSTABLE NOSE BRIDGE
-  DIELECTRIC
-  SOFT TPE
-  SPORTS STYLE
-  TEMPFLEX
-  ULTRA LIGHTWEIGHT

### FEATURES

- + Single wraparound polycarbonate lens
- + Soft, adjustable, anti-slip nose bridge
- + Flexible temple tips
- + Co-injected bi-colour thermoplastic rubber temples provide a secure fit
- + Slim temples enhance comfort when worn with ear defenders
- + 1% metal free
- + Supplied with a microfibre storage pouch
- + Weight: 23g
- + 9.5-Base lens

#### Europe

sales@globus.com  
+44 (0)161 877 4747  
+44 (0)161 877 4746

#### Middle East & Africa

sales.gcc@globusgroup.com  
+971 4 882 9962  
+971 4 882 9963

#### Americas

salesusa@globusgroup.com  
+1 83 337 54747



# RILEY | STREAM EVO

LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
SHADE 5	● RLY00376	5 1 F K N CE / Z87+ W3	R EN166 FT CE UKCA Z87+	Impacts, UV Radiation, Infrared	TECTON 400
IRG	● RLY00374	4 1 F K N CE W4		Impacts, UV Radiation, Infrared	
TWILIGHT	● RLY00364	5-1.7 1 FT CE U6 L1.7 / I 1	R EN166 FT CE UKCA Z87+ AS/NZS 1337.1 Lic. SMK40933	Impacts, UV Radiation	FRIDA 400
INDOOR/OUTDOOR	● RLY00377	5-1.7 1 FT CE / Z87+ U6 L1.7		Impacts, UV Radiation	FRIDA 400, UV400, Moisture Repellent
ANTI-REFLECTIVE	○ RLY00363	2C-1.2 1 FT CE U6 / IO 0		Impacts, UV Radiation	TECTON 400
GREY	● RLY00362	5-2.5 1 FT K N CE U6 L2.5 / I 2		Impacts, UV Radiation, Solar Radiation	
CLEAR	○ RLY00361	2C-1.2 1 FT K N CE U6 / IO 0		Impacts, UV Radiation	
AMBER	● RLY00371	2-1.2 1 FT K N CE U6 / IO 0		Impacts, UV Radiation	
LED	● RLY00369	2C-1.4 1 FT K N CE U6 L1.3 / I 1		Impacts, UV Radiation	
BLUE	● RLY00365	2C-1.4 1 FT K N CE U6 S / I 1		Impacts, UV Radiation	
SHADE 3	● RLY00375	3 1 F K N CE / Z87+ W3 / I 3		Impacts, UV Radiation, Infrared	
TWILIGHT	● RLY00360	5-1.7 1 FT / Z87+ U6 L1.7		Impacts, UV Radiation	
GENERAL SPECIFICATION			COMPONENT SPECIFICATION		

WEIGHT	23g
--------	-----

## PACKAGING

PER BOX	10
PER CASE	200

COMPONENT	MATERIAL
LENS	Polycarbonate
NOSE BRIDGE	Thermoplastic Elastomers (TPE)
TEMPLE	Thermoplastic TR90, Thermoplastic Elastomers (TPE)
HINGE	Thermoplastic TR90, Metal

## ADDITIONAL INFORMATION

<p>CERTIFICATION LEGEND</p>  <p>or click <a href="#">here</a></p>	<p>DECLARATION OF CONFORMITY</p>  <p>or click <a href="#">here</a></p>	<p>VIEW PRODUCT ONLINE</p>  <p>or click <a href="#">here</a></p>
--	---	---

### Europe

sales@globus.com  
+44 (0)161 877 4747  
+44 (0)161 877 4746

### Middle East & Africa

sales.gcc@globusgroup.com  
+971 4 882 9962  
+971 4 882 9963

### Americas

salesusa@globusgroup.com  
+1 83 337 54747

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.  
The manufacturer reserves the right to make any modifications it deems necessary. Published date: 04/06/2026

