



RILEY®

REON

Adjustable face shield rated for high energy impacts

The Reon face shield provides the wearer with 'Class A' face protection. High energy impact resistance to EN 166 'Level A' means that the face shield protects against impacts up to 19m/s (425mph). REON also outperforms for comfort & vision clarity.





CLEAR



SHADE 5



SHADE 3



PANORAMIC
VISION

FEATURES

- + Fitted chinguard
- + Ratchet adjustment allows for a secure fit to a range of head sizes
- + Padded headband for a comfortable fit
- + Adjustable pivot for wearer to select optimum angle
- + Frameless design for a wide, unrestricted field of vision
- + Level A impact resistance - the highest attainable level under EN166
- + Note that browguard and faceshield must be purchased separately.

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110

LENS TYPE	REF	LENS MARKING	FRAME MARKING	PROTECTS AGAINST	COATINGS
	RLY00352			Impacts,UV Radiation,Molten Metal	
CLEAR	RLY00351	2C-1.2 1 AT		Impacts,UV Radiation,Molten Metal	R Anti-Fog
CLEAR	RLY00355	2C-1.2 1 FT		Impacts,UV Radiation	
SHADE 5	RLY00354	5 1 B CE / 1 3		Impacts,UV Radiation,Molten Metal,Infrared	R Anti-Scratch
SHADE 3	RLY00353	3 1 B CE		Impacts,UV Radiation,Molten Metal,Infrared	

GENERAL SPECIFICATION

WEIGHT	360g
--------	------

PACKAGING

PER BOX	1
PER CASE	20

COMPONENT SPECIFICATION

COMPONENT	MATERIAL
LENS	Polycarbonate
HINGE	Metal

ADDITIONAL INFORMATION

CERTIFICATION LEGEND



or click [here](#)

DECLARATION OF CONFORMITY



or click [here](#)

VIEW PRODUCT ONLINE



or click [here](#)

Europe

sales@globus.com
+44 (0)161 877 4747
+44 (0)161 877 4746

Middle East & Africa

sales.gcc@globusgroup.com
+971 4 882 9962
+971 4 882 9963

Americas

Sales@GlobalGlove.com
763-450-0110