

Thanks to stretchable and inclinable temples, LENTA™ is designed to fit the smaller profile. This light frame design offers incredible comfort and protection.

Protection from UVA and UVB light is guaranteed thanks to the high performance TECTON 400 lens coating.

SPECIAL FEATURES

- ✔ Sports style design
- ✔ Adjustable, soft TPE non-slip universal fit nose bridge
- ✔ Fully adjustable temples
- ✔ Supplied with a microfibre storage pouch
- ✔ Weight: 30g
- ✔ 8-Base lens



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00081	2C-1.2 e 1FKN CE	e EN 166 F CE	Impacts, UV radiations	K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
GREY	RLY00082	5-2.5 e 1FKN CE	e EN 166 F CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification

GENERAL SPECIFICATION

LENS BASE	8mm
WEIGHT	30g

PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Dual lens design
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable, adjustable and ventilated
TEMPLE	TR90 Thermoplastic	Inclinable and hard-wearing
HINGE	TR90 Thermoplastic /Metal	Increased flexibility and strength


LENS MARKINGS

LENS FILTER TYPE:

- 2C UV
- 5 Solar

SCALE NUMBER (SHADE):

- 1.2 Clear or Amber
- 2.5 Grey

 Identity of manufacturer


OPTICAL CLASS:

- 1 High optical quality


MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

PERFORMANCE:

- K Resistance to scratches by fine particles
- N Resistance to fogging
-  CE Certification mark

FRAME MARKINGS

 Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s

 CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

