



CUT PROTECTION

**SAPPHIRE ZINC™****HIGH CUT RESISTANT UNCOATED GLOVE MADE WITH ENGINEERED HPPE**

Glass and steel fibre free uncoated gloves offering high cut protection. Can be used as an under glove or worn by itself.

**FEATURES**

- › Cut resistant: Level E (EN 388:2016) / A5
- › Engineered HPPE offers outstanding cut protection
- › Glass and steel fibre free reduce risks of irritation
- › Spandex in the liner allows the glove to fit the hand perfectly
- › Designed for easy movement and continuous wear
- › Breathable to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit
- › Ambidextrous for easy and quick donning

**SUITABLE FOR****Typical Industries**

- Automotive
- Clean room
- Manufacturing
- electronics
- Aerospace

**Suitable Applications**

- Surface control
- Dry conditions works with risks of cut
- Can be worn under a disposable glove or chemical glove

**CERTIFICATION**

See overleaf for explanation





# SAPPHIRE ZINC™

## PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE
	COATING:	Uncoated
COLOUR	Grey	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

## RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00086FB	10 pairs per paper wrap 120 pairs per case
7/S	SKG00086FD	
8/M	SKG00086FF	
9/L	SKG00086FH	
10/XL	SKG00086FJ	
11/XXL	SKG00086FL	

## CERTIFICATION LEGENDS



### MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance		Puncture Resistance	
				Straight Blade Cut Resistance (EN ISO: 13997)	
				Impact Resistance	

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

### CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

### EUROPE

[www.globusgroup.com](http://www.globusgroup.com)

E: [sales@globus.co.uk](mailto:sales@globus.co.uk)

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

### MIDDLE EAST AND AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

E: [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

T: +971 4 882 9962

F: +971 4 882 9963

### GLOBUS AMERICAS

[www.globusgroup.com](http://www.globusgroup.com)

E: [americas@globusgroup.com](mailto:americas@globusgroup.com)



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

©2023 Globus (Shetland) Ltd | SKY-DATA-SAPP-ZINC-0623\_1