



CUT PROTECTION



## CUT RESISTANT, LIGHTWEIGHT PU COATED GLOVE

Extremely flexible and dexterous, yet provides outstanding cut resistance for protection in high cut risk applications. PU coating protects the hand from abrasion and grease while delivering effective long lasting grip.

### FEATURES

- › Cut resistant: Level E (EN 388:2016)
- › Flexible and comfortable while offering great dexterity
- › Steel fibre within the liner provides high level of cut protection for use in high cut risk environments
- › PU coating gives exceptional abrasion resistance while protecting the hand from light oil and grease
- › 13 gauge liner provides a 'second skin' fit for good handling of small parts
- › Reinforced thumb crotch enhances durability
- › Designed for easy movement and continuous wear
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



**LIGHTWEIGHT**  
15gg LINER



### SUITABLE FOR

#### Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Metal Industry

#### Suitable Applications

- Assembling
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics
- Metal Stamping
- Glass Handling

### CERTIFICATION



CAT II



EN 388:2016



4X43E

ASTM / ANSI  
105-2016

CUT

See overleaf for explanation





## PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, steel fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Grey/Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

## RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

## ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SKY00101	10 pairs per bag 120 pairs per case
8/M	SKY00102	
9/L	SKY00103	
10/XL	SKY00104	
11/XXL	SKY00105	

## CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016  
PERFORMANCE LEVELS\*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance		Straight Blade Cut Resistance (EN ISO: 13997)	
		Tear Resistance		Puncture Resistance	
				Impact Resistance	

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

## CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

## EUROPE

[www.globusgroup.com](http://www.globusgroup.com)
E: [sales@globus.co.uk](mailto:sales@globus.co.uk)

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

## MIDDLE EAST AND AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)
E: [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

T: +971 4 882 9962

F: +971 4 882 9963

## GLOBUS AMERICAS

[www.globusgroup.com](http://www.globusgroup.com)
E: [americas@globusgroup.com](mailto:americas@globusgroup.com)

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES  
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

©2022 Globus (Shetland) Ltd | SKY-DATA-SS6-0722\_1