



MULTI-PURPOSE

**NEON XTRA™**

FULL NITRILE COATING

A brightly-coloured and hardwearing fully coated nitrile glove for general handling tasks in oily and dirty conditions.

FEATURES

- › Excellent resistance to abrasion
- › Cotton liner with a lightweight nitrile coating
- › Durable with an excellent grip
- › Warm and comfortable to wear
- › Yellow colouring for increased visibility
- › Anti-bacterial treatment to reduce odours
- › Knitted wrist for a secure fit
- › Seamless liner prevents irritation
- › Ideal for dirty tasks



SUITABLE FOR

Typical Industries

- Agriculture
- Automotive
- Construction
- Highway Maintenance
- Municipal Services
- Repair and Maintenance

Suitable Applications

- Engineering
- General Handling
- Handling Oily Components
- Refuse Collection
- Wet Work

CERTIFICATION

CAT II

EN 388:2016



4111X

See overleaf for explanation



NEON XTRA™

PRODUCT INFORMATION

MATERIALS	LINER:	Cotton
	COATING:	Nitrile
COLOUR	Yellow/White	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SKY222	10 pairs per bag
9/L	SKY223	120 pairs per case
10/XL	SKY224	

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-NEON-XTRA-0420_1