

SKYTEC® | SAPPHIRE™

FLEXIBLE AND LIGHTWEIGHT, CUT LEVEL B GLOVE

The 15 gauge liner and thin palm-dipped PU coating combine to deliver a cut resistant barrier that is ideal for the superior precision handling of sharp components in dry conditions.

FEATURES

- › Cut resistant: Level B (EN 388:2016)
- › Enables precise handling of small components
- › Offers a combination of comfort, dexterity and cut resistance
- › Secure grip in light oily, greasy and dry conditions
- › Excellent resistance to abrasion and rips for extended durability
- › Elasticated wrist provides a secure fit
- › Sanitized® antimicrobial finish provides extra freshness
- › Breathable liner keeps hand cool and helps to reduce perspiration
- › Low linting liner



SUITABLE FOR

Typical Industries

- Construction
- Engineering
- Glass

Suitable Applications

- Assembly
- Bottling/Canning
- Packaging

CERTIFICATION

CAT II

EN 388:2016



3X42B

See overleaf for explanation



PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge HPPE, glass fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Light Blue/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING	VEND COMPATIBLE OPTION	
			CODE	PACKAGING
6/XS	SKY660	10 pairs per bag	SKYV660	120 individually bagged pairs per case
7/S	SKY661		SKYV661	
8/M	SKY662	120 pairs per case	SKYV662	
9/L	SKY663		SKYV663	
10/XL	SKY664		SKYV664	
11/XXL	SKY665		SKYV665	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement.
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight.
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-SAPPHIRE-0620_1