



CUT PROTECTION

SKYTEC®**TRIGATA™**

LIGHTWEIGHT CUT RESISTANT POLYURETHANE COATED GLOVE

A palm-dipped, lightweight glove offering level B cut resistance (EN 388:2016). The thin PU coating allows a secure grip in dry and light oily handling conditions. Ideal for precision handling when protecting against cuts.

FEATURES

- › Cut resistant: Level B (EN 388:2016)
- › Palm-coated polyurethane
- › Lightweight 15 gauge liner
- › Secure grip in dry and light oily handling environments
- › Extremely hardwearing
- › Soft and breathable liner
- › Elasticated knitted wrist provides a secure and comfortable fit
- › Excellent dexterity
- › Sanitized® antimicrobial finish provides extra freshness



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Engineering
- Glass
- Logistics
- Utilities

Suitable Applications

- Assembly
- Bottling/Canning
- Glass Manufacturing
- Handling of objects with sharp objects
- Maintenance
- Metal Fabrication
- Plastics Injection

CERTIFICATION



See overleaf for explanation

Globus®
GROUP

**TRIGATA™****PRODUCT INFORMATION**

MATERIALS	LINER:	15 gauge HPPE, glass fibre, nylon
	COATING:	Polyurethane (PU)
COLOUR	Blue	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKY900	10 pairs per bag 120 pairs per case
7/S	SKY901	
8/M	SKY902	
9/L	SKY903	
10/XL	SKY904	
11/XXL	SKY905	
12/XXXL	SKY906	

CERTIFICATION LEGENDSMECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
					Impact Resistance
					Straight Blade Cut Resistance (EN ISO: 13997)
					Puncture Resistance
					Tear Resistance
					Circular Blade Cut Resistance
					Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

EUROPEwww.globusgroup.com**E:** sales@globus.co.uk**T:** +44 (0)161 877 4747**F:** +44 (0)161 877 4746**MIDDLE EAST AND AFRICA**www.globusgroup.com/gcc**E:** gcc@globusgroup.com**T:** +971 4 882 9962**F:** +971 4 882 9963**GLOBUS AMERICAS**www.globusgroup.com**E:** americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

©2022 Globus (Shetland) Ltd | SKY-DATA-TRIGATA-0722_1