



# RILEY®

## AREZZO

### Low-profile & lightweight safety goggles

Compact & lightweight safety goggle offering protection against liquid droplets as well as impacts. The low-profile design enhances the field of vision & a comfortable fit is guaranteed thanks to the fully adjustable head strap.

○ CLEAR



UNIQUE INNER  
FACE SEAL

### FEATURES

- + Ultra slim design
- + Soft PVC comfort frame
- + Fully adjustable pivoted head strap
- + High performance TECTON 400 anti-scratch & anti-fog protection

#### Europe

sales@globus.com  
+44 (0)161 877 4747  
+44 (0)161 877 4746

#### Middle East & Africa

sales.gcc@globusgroup.com  
+971 4 882 9962  
+971 4 882 9963

#### Americas

Sales@GlobalGlove.com  
763-450-0110

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. Published date: 16/07/2026

GLOBUS



| LENS TYPE | REF      | LENS MARKING              | FRAME MARKING             | PROTECTS AGAINST               | COATINGS   |
|-----------|----------|---------------------------|---------------------------|--------------------------------|------------|
| CLEAR     | RLY00161 | 2C-1.2 1 BT K N / Z87+ U6 | REN166 BT CE UKCA<br>Z87+ | Impacts, Liquid Droplets, Dust | TECTON 400 |

## GENERAL SPECIFICATION

|           |     |
|-----------|-----|
| LENS BASE | 6mm |
| WEIGHT    | 56g |

## PACKAGING

|          |     |
|----------|-----|
| PER BOX  | 5   |
| PER CASE | 100 |

## COMPONENT SPECIFICATION

| COMPONENT | MATERIAL      |
|-----------|---------------|
| LENS      | Polycarbonate |

## ADDITIONAL INFORMATION

CERTIFICATION LEGEND



or click [here](#)

DECLARATION OF CONFORMITY



or click [here](#)

VIEW PRODUCT ONLINE



or click [here](#)

### Europe

sales@globus.com  
+44 (0)161 877 4747  
+44 (0)161 877 4746

### Middle East & Africa

sales.gcc@globusgroup.com  
+971 4 882 9962  
+971 4 882 9963

### Americas

Sales@GlobalGlove.com  
763-450-0110