

REV. 1.0

## REFERENCE MANUAL

### Installation Guide

Please abide by the following illustrations to ensure safety


Please read carefully the relative notice before operation.  
 This manual lists many kinds of marks in detail to avoid injuring body, or suffering loss on property. The marks and explanations are as follows, please keep it in the eyeable place.

**Warning!** It may cause injuring body or damaging object if ignore this mark.  
 ⚠ means "forbidden".

	Do not stand on the toilet cover, and do not place heavy objects on it. (Or else it may cause crack.)	
	Do not clean the toilet seat with household cleaners, volatile, thinner and eradicator, or use nylon brush, and avoid chlorine-containing corrosive and abrasive cleaners. Maintain the shiny surface by using soft fabric and clean water (Or else it may cause abrasion or crack.)	
	Do not let child play the toilet cover, to avoid hurting fingers and other accident.	

### Relative Notice

Open and close toilet seat cover tenderly.  
 (Or else it may cause crack.)





● Toilet seat and cover both have the function of soft closing.


● Closing speed varies for room temperature and usage frequency.

● Please open toilet seat and cover completely, the function of slow closing will fail if let go in the midway, or hurt fingers etc.


Avoid sunlight and other lamp-house irradiate directly. (Or else it may turn colors.)




1. Preparing Seat cover and Bracket with bolts.



2. Fix bolts and nuts suitable hole of Seat cover, then revolve it firmly suitably.




3. Adjust Seat cover to toilet ceramic, revolving bolts, adjust them to tightness.




4. Raising Seat cover, then screwing the bolts.

### Maintenance



#### 1. Periodical maintenance

- Wipe gently with wet fabric.
- Wipe off smut
- Scrub it with neutral cleaners (such as soap powder), and then dry it with clean fabric.



#### 2. Cleaners

- Do not wipe and wash toilet seat cover with abrasive powder.
- Do not use disinfectant, eradicator or other aerosol cleaners.
- Some chemical and cosmetic in bathroom may damage toilet seat cover.