Eastbrook Road, Gloucester GL4 3DB
Technical Helpline: 01452 317890
email: technical@eastbrookco.com

BATHROOM ACCESSORIES - FITTING INSTRUCTIONS AND PRODUCT CARE

Please read the following instructions carefully. Please keep these instructions for future use/reference.

Tools required for installation are:

- Drill with 6mm drill bit.
- Medium flat head screwdriver.
- Spirit level (for double backplate accessories only).

Fitting Accessory to Wall.

- Tip - a piece of masking tape applied to the wall before marking out the fixing holes will stop the drill wandering, particularly on tiled surfaces.
- Position accessory on wall in desired location.
- Mark the two screw positions.
- Remove accessory and drill two holes using a 6mm drill bit to a depth of 30mm.

Caution: *Before drilling, check for hidden power cables and pipes. Take care using power tools, especially near water. The use of a residual current device (RCD) is recommended.*

- Fix accessory to wall using wall plugs and screws provided

Note: *Wall plugs supplied are only suitable for solid stone / brick walls. For plasterboard walls use specialist wall plugs. Seek advice from a specialist about the suitability of fixings to be used.*

Double Backplate Accessories

- For items with two backplates it is important that the distance between them is correct. This can be established as follows:
  - Assemble the product.
  - Offer product up to the wall in the desired location.
  - Mark the screw fixing positions through each backplate.
  - Check markings are exactly horizontal or vertical (depending upon accessory type) with a spirit level
- Fit each backplate to the wall in the marked positions using the process detailed above.

Wall Mirror

- Tightening or loosening the grub screw below the point where the mirror attaches to the accessory body can adjust mirror swivel tension.

Cleaning

We recommend cleaning using a soft damp cloth only. Do not use metal cleaners or other abrasive cleaning agents.

Important Information about Glass Components

Warnings for Glass Products

- A competent person, in accordance with the fitting instructions above, should fit the product.
- WARNING: For safety reasons the product should not be fitted in a shower enclosure or above a bath.
- Do not place very hot or very cold items against or in close proximity to glass surfaces unless adequately thick insulating material is used to prevent such items from coming into contact with the glass.
- Do not strike the glass with hard or pointed items.
- Do not sit or stand on horizontal glass surfaces.
- If a glass component is chipped or broken, replace with glass as specified below. Consult Roper Rhodes with regard to obtaining a manufacturing specification and shape for the replacement glass, quoting the model number.

Glass Shelf

- Maximum safe load for the glass shelf is 5kg.
- Glass shelf is toughened glass, thickness 6mm.