

Tool-less Cross Member Radius Drop

Tool-less Cross Member Radius Drop

The Tool-less Cross Member Radius Drop is designed for compatibility with 1.5" \times 3/8" (38 mm \times 9.53 mm) Stringers and installs without the need for tools, mounting directly to the sides of the runway.

- •Tool-less Cross Member Radius Drops may be positioned over or between the Runway Cross Members
- Use Saf-T-Grips or cable ties, along with the tie-down slots to fully deploy the cable support solutions
- Provides 3" (80 mm) bend radius
- Includes 1.4"H (36 mm), 1" (25 mm) diameter ABS cable spools to separate and guide cables
- Compatible with Universal, TELCO, UL Classified and Adjustable Cable Runway
- Sold individually
- Manufactured from steel; spools are plastic
- For appropriate fit, match Cross Member Radius Drop width to runway width

PATENTED



ORDERING INFORMATION

Part Number	Description	Shipping Weight Ib (kg)
14304-X04	4"W (102), Each, 2 Spools	2 (1.0
14304-X06	6"W (152), Each, 2 Spools	2 (1.0)
14304-X09	9"W (229), Each, 2 Spools	2 (1.0)
14304-X12	12"W (305), Each, 3 Spools	3 (1.5)
14304-X15	15"W (381), Each, 3 Spools	3 (1.5)
14304-X18	18"W (457), Each, 3 Spools	4 (2.0)
14304-X24	24"W (610), Each, 3 Spools	6 (3.0)
14304-X30	30"W (762), Each, 3 Spools	7 (3.0)
14304-X36	36"W (914), Each, 5 Spools	7 (3.0)

X=color: 1=Gray, 5=Clear, 7=Black, E=Glacier White.