



ECOS® Sensor Flushometer

ECOS RESS-C BT-1.1-SF

Product description

1.1 gpf, Dual-Filtered Fixed Bypass Diaphragm, Brushed Stainless Finish, Single Flush, Electrical Override, Battery, ECOS® Exposed Sensor Water Closet Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, BABAA Compliant, cUPC Green Certified, IAPMO, LEED Water, Satisfies LEED Credits)

Code 33754038

Finish

 Brushed Stainless (SF)

Connectivity

 Bluetooth with Sloan Connect App

Downloads

-  Sloan ECOS Single_Dual-Flush Flushometer & Retrofit Valve Installation Instructions.pdf
-  Control Stop Repair and Maintenance Guide.pdf
-  Flush Connections Flanges Repair and Maintenance Guide.pdf
-  Additional Downloads

Videos

-  Sloan Connect App®

Details

- Flush Volume: 1.1 gpf (4.2 lpf)
- Finish: Brushed Stainless (SF)
- Power Type: Battery
- Valve: Diaphragm
- Bypass: Dual-Filtered Fixed Bypass Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Water Closet
- Override: Electrical

Features

- Wireless connected device for real time diagnostic and adjustable product settings
- Sloan Connect App® readily available for smart phone and tablet devices
- User friendly three (3) second Flush Delay
- “Low Battery” Flashing LED
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Four (4) Size AA Battery Power Source
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Electrical specifications

- Arming Delay: 16 seconds

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the ECOS RESS-C BT product?

[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

