

OPTIONS**Flush Volume**

0.5 gpf (1.9 Lpf) (0.5)

1.0 gpf (3.8 Lpf) (1.0)

Finish

Polished Chrome (CP)

Power Type

Hardwired (HW)

Activation

Sensor

Valve

Piston

Water Efficiency

High Efficiency

Low Consumption

Fixture Type

Urinal

Fixture Connection

Top Spud

Installation

Exposed

Override

Less (L/OR)

Control Stop

3/4"

Voltage

24V

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

UL Certified

cUPC Certified

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed


NOTESFor product line drawings, [view model-specific spec sheets](#).

Image for a standard CROWN II 186 ESS shown

DESCRIPTION

Crown® Exposed Sensor Hardwired Urinal Flushometer

FEATURES

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Crown Piston Type Exposed Installation Instructions](#)
- [Crown/Crown II Sensor Activated Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Crown/Crown II Repair and Maintenance Guide](#)
- [Optima ESS Repair and Maintenance Guide](#)
- [Crown Piston Assembly Repair Kit](#)
- [Additional Downloads](#)

VIDEOS

-  ESS Flushometer

All information contained within this document subject to change without notice.