

OPTIONS

Flush Volume

- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)
- 3.5 gpf (13.2 Lpf) (3.5)
- 1.1 gpf (4.2 Lpf) (1.1)
- 2.4 gpf (9.1 Lpf) (2.4)

Finish

- Polished Chrome (CP)
- Stainless Steel (BSS)
- Brushed Stainless (SF)
- Graphite (GR)
- Rough Brass

Power Type

- Hardwired (HW)

Water Efficiency

- Low Consumption
- Water Saver
- High Efficiency

Fixture Connection

- Rear Spud
- Not Included

L Dimension

- 2" - 10 3/4" (51 - 273mm)
- 11" - 12 3/4" (279 - 324mm)
- 13" - 14 3/4" (330 - 375mm)
- 15 3/4" (400mm) (15-3/4-LDIM)
- 18 3/4" (476mm) (18-3/4-LDIM)
- 19 3/4" (502mm) (19-3/4-LDIM)
- 7" - 8 3/4" (178 - 222mm)

Override

- Electrical
- True Mechanical (TMO)
- Less (L/OR)

Wall Box

- Small (SWB)
- With (W/BOX)

Push Button

- C2A (C2A)

Control Stop

- 1" Straight (E)
- Less (L/STOP)



Image for a standard ROYAL 152 ESS shown

DESCRIPTION

Royal® Concealed Sensor Hardwired Water Closet Flushometer

FEATURES

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Royal/Sloan/Crown SWB ESS Installation Instructions](#)
- [Royal ESS Concealed and Exposed Installation Instructions](#)
- [Royal 152/195 ESS TMO Concealed SWB Installation Instructions](#)
- [150/152/190/194/195 ES-SM Installation Instructions](#)
- [Royal ESS Concealed with Wall Box Installation Instructions](#)
- [Royal 152/195 ESS TMO Installation Instructions](#)
- [Royal 152/195 ESS TMO \(Spanish\) Installation Instructions](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

1"

Vacuum Breaker

Less (XYV)

Outlet Tube

Trap Primer (TP)

Voltage

24V

Adapter

28mm Sweat Solder Adapter Kit

Special Features

Whitworth Thread (WWT)

Less Logo (LL)

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

UL Certified

cUPC Certified

UPC Certified

Satisfies LEED Credits

cUPC Green Certified

WaterSense Listed

BREEAM Water Credit

- [Royal 152/195 ESS TMO SBX Installation Instructions](#)
- [Royal 152/195 SWB ESS TMO \(Spanish\) Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Optima ESS Repair and Maintenance Guide](#)
- [Optima ESS TMO Concealed Repair and Maintenance Guide](#)
- [Optima ESS TMO SWB Concealed Repair and Maintenance Guide](#)
- [Royal ESS SWB Repair and Maintenance Guide](#)
- [Flushometer Pressure gauges](#)
- [Additional Downloads](#)

VIDEOS

-  [ESS Flushometer](#)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.