

AER-DEC® Sink

AD-84000 BASYS®

Product description

AER-DEC® 4-Station Wall-Mounted Sink.

Compliances & Certifications



(ADA Compliant, BAA Compliant, cUPC Certified, IGC 156)

Code AD-84000 BASYS®

Downloads

- [AER-DEC® BASYS® Installation Instructions.pdf](#)
- [AER-DEC® 80000 Series Repair and Maintenance Guide.pdf](#)
- [AER-DEC® Brochure.pdf](#)
- [Sink Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan AER-DEC](#)

Details

- Material:
 - Corian
 - Quartz
 - Width: 120" (3048mm)
-

Features

Four-Station Lavatory System with the following features:

- Built in patented airdam technology that eliminates backsplash and updrafts
 - A monolithic console available in Corian® or quartz
 - Basins can be sized to project requirements
 - Many customization options - see Configurator.Sloan.com for all options
 - Deck mounted dryer with HEPA filter technology minimizes the risk of slip and fall from water on the bathroom floor
 - ADA compliant design and IAPMO certification for commercial load and drain requirements
 - Includes deck mounted BASYS style hand dryers standard, available in all of Sloan's finishes
 - Pairs great with Sloan BASYS faucets and soap dispensers, available in all of Sloan's finishes
-

Colors

For a complete list of Corian® colors:

<http://www.corian.com/~colors-of-corian-r->

For a complete list of Corian® quartz colors:

<https://www.corianquartz.com/~colors-of-quartz->

Recommended specifications

Sloan AER-DEC Integrated Sink System model no. AD 8X000. Product to be fabricated out of Corian or quartz. Supplied with Sloan EHD-510 deck mounted hand dryer, Sloan EFX Series automated sensor faucet, and Sloan ESD-400 or ESD-500 sensor operated foam soap dispenser. Supplied with Basin that includes patented Airdam for hand dryer performance and HEPA filter included with hand dryer. Sink design to be ADA compliant. Supplied with enclosure.

Suggested Faucets

This sink is compatible with [BASYS®](#)

Warranty


[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.


Many customization options - see [architectural worksheet](#) for all options.

Rough-In (Four Station): Plumbing and Electrical, front View



- Notes:
1. Hot and cold water supply line location subject to local codes.
 2. Hand Dryer Motor alone, without heater option activated, is only 500 watts or less with speed control.
 3. Hand Dryer with heater requires 1000 watts or less with speed control.
 4. Each Hand Dryer Motor shall be plugged into a dedicated 20 amp GFI safety circuit.
 5. Hand Dryer Motor to have a dedicated circuit with power cord and grounded plug.
 6. Each Faucet and Soap Dispenser requires a dedicated 15 amp GFI safety circuit.
 7. Cut backing to allow for electrical and plumbing components.
 8. Electrical boxes need to be vertically, flush mounted to backing material, to allow for plumbing and component clearance.
 9. Electrical outlets can fit either two outlet junction boxes or one quad outlet junction box.

Rough-In (Four Station): Section View



- Notes:
1. Backing material should equal thickness of drywall, 1/2" min.
 2. Angled enclosure shown, rough-in dimensions for vertical enclosure are the same.