



Sloan® FLITE-DEC® Soap Dispenser

ESD-1100-CP

Product description

Polished Chrome Finish, 2000 ml, Sloan® Basin-Mounted Top-fill Soap Dispenser.

Compliances & Certifications



(WELL Building Standard)

Code 33461078

Finish



Polished Chrome (CP)

Downloads

- [ESD-1100 Installation Instructions.pdf](#)
- [ESD-1100 Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Polished Chrome (CP)
- Power Type: Battery
- Height: 1.125" (29mm)
- Width: 2.25" (57mm)
- Sensor Type: IR
- Soap Type: Foam
- Soap Color: Clear
- Soap Scent: Unscented
- Bottle Size: 2000 ml

Features

Sensor Activated, Electronic, Polished Chrome Finish, Machined Brass Body, Hand Washing Foam Soap Dispenser with the following features:

- Mounts to basin wall
- 2.85 Gallon Reservoir
- Can withstand up to 150lbs of downward force applied to front of spout
- Top-fill refill quick connect
- Soap Reservoir supplies one soap dispenser
- Low Soap Level Indicator
- All electronics sealed
- Double infrared sensors with automatic setting feature
- Foaming Soap Refill (not included)

Recommended specifications

Sloan ESD-1100 Top-Fill FLITE-DEC Soap Dispenser. Must include 2000 ml Reservoir. Soap Dispenser to have Polished Chrome finish. Must be supplied with 2 bottles of 2000ml Purell(R) REDIFOAM soap. Must be a closed soap system to eliminate the risk of overflowing and contamination of the reservoir. Soap Dispenser must be able to withstand up to 150lbs. of downward force.

Soap Refills

- ESD-347 (2000 ml)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

