



Sloan® XLERATOR® Hand Dryer

EHD-502-CP-HEPA

Product description

EHD-502, HEPA, 208/277V, Sloan® XLERATOR® Sensor-Operated Wall-Mounted Hand Dryer.

Compliances & Certifications



(BAA Compliant, cUL Certified, EPD, Proposition 65, UL Certified, WELL Building Standard)

Code 3366053

Finish

 Polished Chrome (CP)

Downloads

- [Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions .pdf](#)
- [Hand Dryer Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Polished Chrome (CP)
- Voltage: 208/277V
- Wattage: 50/60Hz
- Amperage: 5.6A-6.2A
- Mounting: Wall-Mounted
- Power Type: Hardwired
- Depth: 6.6875" (322mm)
- Height: 6.6875" (170mm)
- Width: 11.75" (298mm)

Features

- Automatically operates by means of an Infrared Optical Sensor with 35-second lockout feature, it activates a strong controlled air blast
- Residual moisture is evaporated with a warm stream of air up to 135°F/57°C
- One-piece heavy-duty rib reinforced die cast zinc alloy housing minimizes damage to dryer in abusive environments
- 95% cost savings vs. paper towels
- Can be easily positioned to comply with ADA requirements or for juvenile height
- Series commutated, through-flow discharge, vacuum type motor/ blower combination
- Air velocity of 16,000 LFM (linear feet per minute) at an outlet temperature of 135°F/57°C at a 72°F/22°C ambient room temperature
- Heating element constructed of Nichrome wire and protected by an automatic resetting thermostat
- One piece heavy-duty rib reinforced die cast zinc alloy housing
- Bright chrome plate or chip-proof electrostatically-applied epoxy finish, available in Polished White, Matte White, Polished Chrome, Brushed Nickel and Graphite
- Tamper-proof cover fasteners are included, Virtually maintenance free
- Decibel Rating of 78-80 dB
- 8 second dry time, Hygienic hand dryer solution
- Adjustable speed, sound and heat control
- Available with Recess Kit for ADA compliance
- Available with HEPA Filtration System proven to remove 99.97% of potentially present bacteria at 0.3 microns from the air

Recommended specifications

Sloan Xlerator Sensor Operated Hand Dryer. 208V/230V Polished Chrome Finish.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.



