

OPTIONS

Flush Volume

- 0.125 gpf (0.5 Lpf) (0.125)
- 0.5 gpf (1.9 Lpf) (0.5)
- 0.25 gpf (0.9 Lpf) (0.25)
- 1.0 gpf (3.8 Lpf) (1.0)

Power Type

- Hardwired (HW)
- Battery

Water Efficiency

- High Efficiency
- Low Consumption

Bypass

- Dual-Filtered Bypass

Compliances & Certifications

- ADA Compliant
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- Satisfies LEED Credits
- cUPC Green Certified
- BAA Compliant
- BABAA Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ECOS RESS-U shown

DESCRIPTION

ECOS® Exposed Sensor Urinal Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037.
- Chrome plated metal handle cap

DOWNLOADS

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [ECOS HW Repair and Maintenance Guide](#)
- [Additional Downloads](#)